



WIRELESS DOOR CONTROLS

DOOR ACTIVATION DEVICES

KINETIC BY CAMDEN™: 900MHZ. NO-BATTERY WIRELESS DOOR CONTROL SYSTEM



Kinetic by Camden™ is an advanced 900 MHz, 'power harvesting' wireless system that uses the energy created by the operation of the switch to power the wireless transmitter. It avoids the need to provide power or batteries, saving installation and maintenance costs.



Features	
<ul style="list-style-type: none"> • Huge savings in installation costs • No-battery maintenance • Environmentally friendly - Eliminates the disposal of batteries 	<ul style="list-style-type: none"> • Fits standard depth mounting boxes • Smooth switch operation, ADA Compliant Activation, 3.4 lbs force

KINETIC BY CAMDEN™ PUSH PLATE SWITCH SERIES MODELS

See product series catalog pages 68-74 for graphic options and ordering information

CM-25K	1-3/4" Width, Narrow push plate switch, vertical mounting, brush stainless steel finish
CM-25HK	1-3/4" Width, Narrow push plate switch, horizontal mounting, brush stainless steel finish
CM-26CBK	1-3/4" Width Narrow push plate switch, blue with white graphics, exposed screws
CM-35K	2" Width Narrow push plate switch, single gang back plate brushed stainless steel finish
CM-35NK	2" Width Narrow push plate switch, vertical mounting, brushed stainless steel finish
CM-40K	4-1/2" Round push plate switch, brushed stainless steel finish
CM-41K	4-1/2" Round push plate switch, brushed stainless steel finish
CM-60K	6" Round push plate switch, brushed stainless steel finish
CM-45K	4-1/2" Square push plate switch, concealed screws, brushed stainless steel finish
CM-46K	4-1/2" Square push plate switch, exposed screws, brushed stainless steel finish
CM-46CBK	4-1/2" Square push plate switch, exposed screws, aluminum, blue paint finish
CM-7536K	36" Long Column™ push plate switch anodized aluminum, optional bronze/blue finish
CM-7536SSK	36" Long Column™ push plate switch anodized aluminum, stainless steel finish
CM-2520K	Double Gang Vestibule Push Plate Switch with /4AL, /4AR Graphics

Push Plate Switch & No-Battery Transmitter

Wireless Frequency: 900 MHz. Fixed Frequency

Range Open Air: Up to 300ft.

In Operator Header: Up to 70ft.

Temp Rating: -40°F to 185°F (-40°C to +85°C)

Water Tight Option: Yes

Dimension: 1-1/2" (38mm) Box Depth Required



CM-RX-90

KINETIC BY CAMDEN™ RECEIVER See pg 78 for specifications		List Price
■ CM-RX-90	Advanced, Compact Single Relay Receiver	\$90.00