

CV Series Proximity Readers and Credentials



ADVANCED
TECHNOLOGY

Camden sets the electronic security benchmark for 125 kHz proximity readers, cards and tags.

Proximity readers interface with a wide range of electronic access control systems by complying with Wiegand and ABA Track II magnetic stripe formats or bi-directional Open Supervised Device Protocol (OSDP).

In addition, our cards and tags eliminate maintenance by requiring no battery and can be ordered to support several proximity reader technologies.

Features

- Mullion and single gang Wiegand reader models
- IP67 rated weather and vandal resistant
- 125 kHz proximity reader
- Up to 8 inches (202 mm) read range
- LED and audible confirmation
- A range of HID 37 bit and AWID 34 bit compatible cards / tags available
- 3 year warranty



SPECIFICATIONS

INPUT VOLTAGE: 5 - 16 VDC

CURRENT: **CV-7400** 30 mA typical, 75 mA peak @ 12 VDC
CV-7820 35 mA typical, 75 mA peak @ 12 VDC

FREQUENCY: 125 kHz

CABLING: 24 AWG minimum, multi-conductor stranded with overall foil shield

INTERFACE: Wiegand, ABA Track II magnetic strike (clock & data) or OSDP

OPERATING TEMPERATURE: -31°F to 150°F (-35°C to 66°C)

OPERATING HUMIDITY: 0% to 90% relative humidity

LED CONTROL: Four-state standard (red, green, amber and off)

INSTALLATION: Electronics sealed in weather / tamper-resistant epoxy potting

MOUNTING: **CV-7400** Mullions, including metal doors, window frames and flat surfaces
CV-7820 Metal or plastic single gang wall box and flat surfaces

READ RANGE: **CV-7400** Up to 5" (126mm) | **CV-7820** Up to 8" (202mm)









AUDIO TONE: Beeper included

PROTECTION: IP67



WEIGHT: **CV-7400** 3oz (85g) | **CV-7820** 4oz (113g)

DIMENSIONS: **CV-7400** 1-3/4" W x 3-1/5" H x 7/10" D (43mm x 81mm x 18mm)
CV-7820 3" W x 4-3/5" H x 2/5" D (76mm x 117mm x 10mm)

ORDERING INFORMATION

Proximity Readers		HID Prox Cards & Key Tags		AWID Prox Cards & Key Tags	
 CV-7400	Narrow, compact, 4 - 5" read range	 CV-ISH CV-ISH-B	HID ISO prox card, 10 pack HID ISO prox card, 100 pack	 CV-CSA CV-CSA-B	AWID prox card, clam shell style, 10 pack AWID prox card, clam shell style, 10 pack
 CV-7820	Single gang, up to 8" read range	 CV-CSH CV-CSH-B	HID clam shell prox card, 10 pack HID clam shell prox card, 100 pack	 CV-ISA CV-ISA-B	AWID ISO prox card, 10 pack AWID ISO prox card, 100 pack
		 CV-KTH	HID prox key tag, 25 pack	 CV-KTA	AWID format prox key tag, 25 pack

DIMENSIONS

CV-7400	CV-7820
 <p>Front view: 1-3/4" (43mm) width, 3" (76mm) height</p> <p>Side view: 7/10" (18mm) depth</p>	 <p>Front view: 3" (76mm) width, 4-5/8" (118mm) height</p> <p>Side view: 1/2" (12mm) depth</p>



Opening New Doors to Innovation, Quality, and Support!

2395 Skymark Ave, Mississauga, ON Canada L4W 4Y6 • Toll Free: 1(877) 226-3369 (CAMDEN9)
 Tel: (905) 366-3377 | Fax: (905) 366-3378 | E-mail: info@camdencontrols.com | www.camdencontrols.com



Part #: MKTG-LIT-SP-CRED-R1