



CX-ED1579L

**'ALL IN ONE' FIRE RATED
ELECTRIC STRIKE**

STANDARD FEATURES	CAMDEN 1579L	HES1006	HES1500	HES1600	RCI F2164	VON DUPRIN 4400	VON DUPRIN 6210	SEC-LARM SD-996C	LOCKNETIS MS-100	LOCKNETIS MS-100F
Accommodate Cylindrical and Mortise Locksets	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Supplied with Face Plates	✓	Options	Options	Options	✓	✓	✓	✓	✓	✓
Accommodate Deadbolts	✓	✓	✓	✓	✓	✓	X	✓	✓	✓
Release and capture deadbolts	X	✓	X	X	X	X	X	X	X	X
Strike body depth	1-5/8"	1-11/16"	1-3/8"	1-5/8"	1-5/8"	1-5/8"	1-5/8"	1-13/16"	1-13/16"	1-13/16"
Strike cavity	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/4"	3-1/8"	3-1/8"	3-1/8"
Stainless steel construction	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Static strength (Lbs.)	1800	3700	1500	1500	1500	1500	1500	1000	1000	1000
Dynamic strength	70	350	70	70	70	70	70	33	70	70
Endurance-Cycles	2M	1M	1M	1M	2M	2M	1M	250,000	250,000	250,000
Field Selectable Fail Safe-Fail Secure	✓	X	X	X	✓	✓	X	✓	✓	✓
Non handed	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Easy install shims to improve locking	✓	X	X	X	X	X	X	X	X	X
Horizontal Adjustment	Y- Shims Required	Y- Shims Required	✓	✓	Y- Shims Required	Y- Shims Required	Y- Shims Required	Y- Shims Required	Y- Shims Required	Y- Shims Required
Plug in connectors	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Trim Plate for keepers included	✓	✓	✓	✓	✓	✓	X	✓	✓	✓
Lip extension	X	✓	✓	✓	X	X	X	X	X	X
Latch bolt monitor	Standard	Cost Option	Cost Option	Cost Option	Cost Option	Cost Option	Cost Option	X	X	X
Install template/jig	✓	✓	✓	✓	X	X	X	X	X	X
Frame types	All	All	All	All	All	All	All	All	All	All
UL-10C 3 Hour Fire rated	✓	✓	✓	✓	✓	✓	✓	X	X	90-Min
UL-1034 Burglary listed	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Dual voltage 12-24	✓	✓	✓	✓	✓	✓	X	✓	✓	✓
AC/DC	✓	X	X	X	✓	✓	X	X	X	X
Continuous duty	✓	✓	✓	✓	✓	✓	✓	X	X	X
POE friendly	✓	X	✓	✓	✓	✓	X	✓	✓	✓
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 years	3 years	3 years	3 years

Note: Specifications are subject to change without notice..... JANUARY 2, 2020

MKTG-LIT-PRODCOMP-1579